

Technical Data Sheet

Issue: 07/2023/v01

Product-Line: WRT-V
Material: Soft vinyl yellow glossy
TEXTIT-Material-Code: TMC-1004

Material data:

Face material	PVC-film yellow glossy Thickness: 70 μ \pm 6 μ m
Adhesive	Acrylic dispersion, permanent, solvent free Adhesive grammage: ca. 18 g/m ²
Liner	Release liner white Thickness: 55 μ m \pm 5 μ m – Grammage 63 g/m ² \pm 5 g/m ²
Printing	Thermaltransfer / flexographic / letterpress / screenprinting
Application temperature*	+ 10 °C (+ 50°F) to + 40 °C (+ 104°F)
Temperature range*	- 40 °C (- 40°F) to + 80 °C (+ 176°F)
Adhesion*	Glas 25 N/25 mm (FINAT FTM 1 – adhesion, contact time 24 hours) <ul style="list-style-type: none">• Glas 13 N (FINAT FTM 9 – Loop tack)• Steel 4 hours (FINAT FTM 8 – Shear adhesion)
Environmental performance	Oil, household cleaner, alcohole, humidity (95%), water, light acids
RoHs-compliant	yes
Shelf live	Two years from date of manufacture of product when properly stored at +22°C (+ 72°F) and 50% relative humidity (+/- 5%) No direct sun exposure
Typical physical properties	Durable and weather-proof labels (for interior and outside applications) – no direct sunlight Electrically not conductive

* typical data (all surfaces should be clean and dry, free of fat and oil. For best conditions, application surface should be at room temperature or higher)